



SHADOW

Ref. 07200040

RICETRASMETTITORE PMR446

- Ultra-small size design
- Easy to use
- Monitor function
- 3,7V/1200mAh Li-ion battery
- PC functions manageable:
 - 50 CTCSS and 83 DCS codes
 - Squelch treshold level
 - TOT (Time-Out-Timer) function
 - BCL (busy channel lock) function
- Power Save function

Supplied with: 3,7V/1200mAh Li-ion battery, battery charge, belt clip, italian and english user manual

Technical specification

| | |
|-----------------------------|---------------------------|
| Frequency range | 446.00625 ~ 446.09375 MHz |
| Channel | 8 + 8 channels |
| Modulation | FM |
| Operating temperature range | -15°C ~ +55°C |
| Voltage | 3.7V |
| Standby current | about 15mA |
| Size | 90 × 50 × 28 mm |
| Weight | 160g |
| Transmitter | |
| Frequency stabilization | ±5ppm |
| Output power | 500 mW |
| Emission current | ≤450mA |
| Maximum frequency deviation | ±2.5 |
| Audio distortion | <10% |
| Receiver | |
| Sensitivity | <-122dBm (12dB SINAD) |
| Audio output | ≥500mW |
| Receiving current | ≤350mA |
| Audio distortion | <10% |